

FULLY INTEGRATED GENERATOR SETS

YBLP 150 - LP665G2

COMPLETE DIESEL GENERATOR SET

I S S U E 2 0 2 3

CONTENT

| DESCRIPTION | ' |
|-----------------------|---|
| FEATURES | ı |
| GENSET SPECIFICATIONS | ı |
| ENGINE SPECIFICATIONS | 2 |
| ALTERNATOR SPECS | 2 |
| CONTROL SYSTEM | 2 |
| GENSET OPTIONS | 2 |

POWER RATING

RATING - 50HZ, I500 RPMPRIME RATING STANDBY RATING

KW KVA

165

132

KW KVA

120 150

DATA SHEET SPECIFICATION 150KVA - 165KVA - 50

HZ



Description

Younes Bros generators are fully designed to maintain optimum performance and reliability using the finest solutions for technical simplicity and robust construction

Our generators are available with **CE** certification along with the installation Quality Assurance (**IQA**) from

Lister Petter and designed in facilities certified to ISO 9001



YBLP 150- LP665G2



Features

- Lister Petter heavy duty engines
- Leroy Somer Class H Alternators
- Deep Sea control system
- Water cooling system
- Optional weather / sound protective enclosures
- Genset accepts load as per NFPA110

Genset Specifications

Generating set KVA Prime I50 KVA Standby I65 KVA, equipped with Lister Petter diesel engine type LP665G2 driving at I500 RPM.

A single bearing Leroy Somer alternator brushless, self excited, self regulated, insulation and temperature class H, PH 0.8, 230/400V, 3 phase, 4 wire regulated at +/-1%, 50 Hz.



THE POWER OF INDEPENDENCE www.younesbros.com

2023 - YOUNES BROS s.a.r.l - All rights reserved Specifications subject to change without prior notice

YBLP 150 - LP665G2

YOUNES#BROS

COMPLETE DIESEL GENERATOR SET

ISSUE 2023

Engine Specifications

BRAND LISTER PETTER **TYPE** LP665G2 150 KVA Output prime rating Displacement 6.5 Liter No of cylinders 6 Ambient Temperature 55°C 105 mm Bore Stroke 124 mm Cycle 4 Stroke

Aspiration Turbocharged and air-to-air intercooled

1500 RPM Running speed

25% - 9.9 liter/hour Fuel Consumption

50% - 17.6 liter/hour 75% - 25.2 liter/hour 100% - 33.1 liter/hour

Type of governor Electronic Type of Injection Direct







Alternator Specifications

Control System

Brand Leroy Somer 400 V Rated Voltage

3 Phase 1500 RPM Rotational Speed

Power Factor 8.0 Frequency 50 Hz



Deep Sea Automatic Start Control module that offers an advanced range of engine monitoring and protection

features

Generator Set Options

Warranty: 5 Years for standby application Water jacket heater 230V **Engine:**

Enclosure: Sound attenuated canopy

Silencer: Alternator: Alternator Heater

PMG kit

Power Panel: 4 Poles Main Circuit Breaker

2 Years for prime application

9 dB attenuation industrial silencer

25 dB residential - delivered loose

Younes Bros s.a.r.l

Address: Nahr El Mott - Main Road - Beirut - Lebanon

00961-1-887886-901488-902488 Contact us:

Fax: 00961-1-901588

Email: info@younesbros.com



THE POWER OF INDEPENDENCE

www.younesbros.com

2023 - YOUNES BROS s.a.r.l - All rights reserved Specification subject to change without prior notice

